

§ 72.15-15

at the end opposite from that at which the inlet ducts are fitted.

(g) All ducts shall be constructed of non-ferrous metal or galvanized ferrous metal not less than No. 22 USSG, intact and gastight from end to end and shall be of substantial construction. The ducts shall lead as direct as possible and be properly fastened and supported.

(h) All supply ducts shall be provided with cowls or scoops having a free area not less than twice the required duct area. When the cowls or scoops are screened, the mouth area shall be increased to compensate for the area of the screen wire. Dampers shall not be fitted in the supply ducts. Cowls or scoops shall be kept open at all times except when the stress of weather is such as to endanger the vessel if the openings are not temporarily closed. Supply and exhaust openings shall not be located where the natural flow of air is unduly obstructed, or adjacent to possible sources of vapor ignition, nor shall they be so located that exhaust air may be taken into the supply vents.

§ 72.15-15 Ventilation for closed spaces.

(a) All enclosed spaces within the vessel shall be properly vented or ventilated. Means shall be provided to close off all vents and ventilators.

(b) Means shall be provided for stopping all fans in ventilation systems serving machinery and cargo spaces and for closing all doorways, ventilators and annular spaces around funnels and other openings to such spaces, from outside these spaces, in case of fire.

(c) The ventilation of spaces which are "specially suitable for vehicles" shall be in accordance with the provisions of this paragraph. In addition, if vehicles are operated inside of enclosed spaces, the ventilation shall be in accordance with subpart 78.83 of this subchapter.

(1) Areas below the weather deck shall be provided with continuous pressure-positive ventilation at each level on which vehicles are transported.

(2) The quantity of ventilating air shall be not less than 1 cubic foot per minute per square foot of deck area.

46 CFR Ch. I (10-1-07 Edition)

(3) The ventilation shall be such as to prevent air stratification as well as to prevent accumulation of air pockets.

(4) An alarm system shall be provided which will indicate the loss of required ventilation. The alarm location shall be in a normally manned space acceptable to the Commandant.

[CGFR 66-50, 30 FR 16903, Dec. 30, 1965, as amended by CGFR 66-33, 31 FR 15281, Dec. 6, 1966]

§ 72.15-20 Ventilation for crew quarters and passenger spaces.

(a) All crew and passenger spaces shall be adequately ventilated in a manner suitable to the purpose of the space.

(b) On vessels of 100 gross tons and over, except for such spaces as are so located that under all ordinary conditions of weather, windows, ports, skylights, etc., and doors to passageways can be kept open, all crew spaces shall be ventilated by a mechanical system, unless it can be shown that a natural system will provide adequate ventilation. However, vessels which trade regularly in the tropics shall, in general, be fitted with a mechanical ventilation system.

§ 72.15-90 Vessels contracted for prior to November 19, 1952.

(a) Existing arrangements previously approved will be considered satisfactory so long as they are maintained in good condition to the satisfaction of the Officer in Charge, Marine Inspection. Minor repairs and alterations may be made to the same standards as the original design provided that in no case will a greater departure from the standards of §§ 72.15-5 through 72.15-20 be permitted than presently exists.

(b) [Reserved]

Subpart 72.20—Accommodations for Officers and Crew

SOURCE: CGD 95-027, 61 FR 26002, May 23, 1996, unless otherwise noted.

§ 72.20-1 Application.

The provisions of this part, except §§ 72.20-90, apply to all vessels contracted for after November 18, 1952. Vessels contracted for before November

Coast Guard, DHS

§ 72.20-30

19, 1952, must meet the requirements of § 72.20-90.

§ 72.20-5 Intent.

Accommodations provided for officers and crew on all vessels shall be securely constructed, properly lighted, heated, drained, ventilated, equipped, located, arranged, and insulated from undue noise, heat, and odors.

§ 72.20-10 Location of crew spaces.

(a) Crew quarters must not be located farther forward in the vessel than a vertical plane located at 5 percent of the vessel's length abaft the forward side of the stem at the designed summer load water line. However, for vessels in other than ocean or coastwise service, this distance need not exceed 8.5 meters (28 feet). For the purpose of this paragraph, the vessel's length must be as defined in § 43.15-1 of subchapter E (Load Lines) of this chapter. Unless approved by the Commandant, no section of the deck head of the crew spaces may be below the deepest load line.

(b) There must be no direct communication, except through solid, close fitted doors or hatches between crew spaces and chain lockers, or machinery spaces.

§ 72.20-15 Construction.

All crew spaces are to be constructed and arranged in a manner suitable to the purpose for which they are intended and so that they can be kept in a clean, workable, and sanitary condition.

§ 72.20-20 Sleeping accommodations.

(a) Where practicable, each licensed officer shall be provided with a separate stateroom.

(b) Sleeping accommodations for the crew must be divided into rooms, no one of which shall berth more than 4 persons.

(c) Each room shall be of such size that there is at least 2.78 square meters (30 square feet) of deck area and a volume of at least 5.8 cubic meters (210 cubic feet) for each person accommodated. The clear head room shall be not less than 190 centimeters (75 inches). In measuring sleeping accommodations any furnishings contained therein for

the use of the occupants are not to be deducted from the total volume or from the deck area.

(d) Each person shall have a separate berth and not more than one berth may be placed above another. The berth must be composed of materials not likely to corrode. The overall size of a berth must not be less than 68 centimeters (27 inches) wide by 190 centimeters (75 inches) long, except by special permission of the Commandant. Where two tiers of berths are fitted, the bottom of the lower berth must not be less than 30 centimeters (12 inches) above the deck. The berths must not be obstructed by pipes, ventilating ducts, or other installations.

(e) A locker must be provided for each person accommodated in a room.

§ 72.20-25 Washrooms and toilet rooms.

(a) There must be at least 1 toilet, 1 washbasin, and 1 shower or bathtub for each 8 members or portion thereof in the crew who do not occupy sleeping accommodations to which private or semi-private facilities are attached.

(b) The toilet rooms and washrooms shall be located convenient to the sleeping quarters of the crew to which they are allotted but must not open directly into such quarters except when they are provided as private or semi-private facilities.

(c) All washbasins, showers, and bathtubs must be equipped with adequate plumbing, including hot and cold running water. All toilets must be installed with adequate plumbing for flushing.

(d) At least 1 washbasin must be fitted in each toilet room, except where private or semi-private facilities are provided and washbasins are installed in the sleeping rooms.

(e) Where more than 1 toilet is located in a space or compartment, each toilet must be separated by partitions.

§ 72.20-30 Messrooms.

(a) Messrooms must be located as near to the galley as practicable except where the messroom is equipped with a steam table.

(b) Each messroom must seat the number of persons expected to eat in the messroom at one time.